

COMMAND 200 Series

SC 260 ATC/C3 UT
SC 260 ATC/C3 AG
SC 260 ATC/C3
SC 230 ATC/C3 AG
SC 230 ATC/C3

In control and present

Give and receive commands with consistent call clarity and stay aware of your environment while multi-tasking. Meet the daily challenges of ATC and C3 situations with robust, lightweight headsets – either single or double sided – for all-day comfort and protection from acoustic injury.

Hearing and being heard clearly is vital for safety and confidence in ATC/C3 environments. Thanks to the truly premium audio experience of this series, ATC and C3 operators can perform with reliable excellence. The noise-cancelling microphone filters out background noise in busy operations rooms and the headset is also designed for situational awareness when surrounding conversations are essential to maintain control. A fully adjustable metal headband and soft leatherette ear cups ensure a perfect fit so you can stay focused on the task at hand.

See more at eposaudio.com/command-sc200



Key benefits & features

Consistent communication with EPOS Voice™ technology

Voice enhancing technology with noise-cancelling microphone delivers clear voice transmission and reception for listeners

Protect your hearing with EPOS ActiveGard®

Guards against acoustic injury caused by sudden sound bursts on the line without risk of communication drop-out

Multitask with two channel stereo application

Enabling multi-channel communication when switching between air and land-based calls on SC 260 ATC/C3 AG

All-day comfort and robust build

Made from high-quality materials, the CircleFlex™ dual-hinge ear cup system and adjustable headband create a perfect fit

Choose your wearing style

With a flexible microphone boom arm worn on either the left or right

COMMAND 200 Series

Product data

General

Contact pressure	1.9 N
Ear coupling	Supra-aural (On Ear)
Cable length	1.0 m / 3.28 ft
Weight of headset	SC 230: 58 g/2.05 oz, SC 260: 86 g/3.04 oz
Storage temperature	-55 °C - +70 °C
Operating temperature	-15 °C - +55 °C
Connector*	Mini-XLR
Weight of headset with cable	SC 230: 69 g/2.43 oz, SC 260: 97 g/ 3.42 oz
Warranty	2 years

Mircophone

Microphone type	Electret, noise-cancelling
Sensitivity	-38 dBV/Pa (12.6 mV/Pa) @ 1 KHz, +/- 3 dB
Supply voltage	1-10 V DC
Frequency response	150 - 6,800 Hz

* SC 260 ATC/C3 UT is unterminated

Packaging

Dimension of product packaging (W x H x D)	153 x 200 x 59 mm / 6.03 x 7.88 x 2.32 in
Package weight (incl. complete product and packaging)	SC 230: 177 g / 6.24 oz, SC 260: 205 g/7.23 oz
Units in distributor master carton	20
Master carton weight incl. products	SC 230 4.5 kg / 9.92 lbs, SC 260 5.2 kg / 11.46 lbs
Dimension of master carton (W x H x D)	352 x 315 x 416 mm / 13.87 x 12.41 x 16.39 in
Unit pack/end user	1

Content of delivery

Box content	Headset, leatherette ear pads, mounted on headset, cable/clothing clip, mounted, nylon carry pouch
-------------	--

COMMAND 200 Series

Product data

Product	SC 230 ATC/C3 AG	SC 230 ATC/C3	SC 260 ATC/C3 AG	SC 260 ATC/C3	SC 260 ATC/C3 UT
Art. no.	1000294	1000295	1000292	1000293	1000291
EAN code	57 14708 00095 2	57 14708 00092 1	57 14708 00093 8	57 14708 00094 5	57 14708 00096 9
UPC code	8 40064 40095 4	8 40064 40092 3	8 40064 40093 0	8 40064 40094 7	8 40064 40096 1
Wearing style	SC 230: Headband with side-support. SC 260: Headband.				

Headphones

Sound pressure level:

dB SPL @ 1 kHz, 0.5 V	103*	103	103*	103	103
dB SPL @ 1 kHz, 1 mW	88	88	86.5	86.5	86.5
dB SPL @ 1 kHz, 1V	95,5	95,5	99,5	99,5	99,5
Max SPL	103 dB	114 dB	113 dB	114 dB	114 dB
THD, total harmonic distortion SPL at 1 kHz	<1 % at 102 dB SPL at 1 kHz	<1 % at 102 dB SPL at 1 kHz	<1 % at 102 dB SPL at 1 kHz	<1 % at 102 dB SPL at 1 kHz	<1 % at 102 dB SPL at 1 kHz
Frequency response	50 – 18,000 Hz	50 – 18,000 Hz	50 – 18,000 Hz	50 – 18,000 Hz	50 – 18,000 Hz
Impedance	200 Ω	200 Ω	200 Ω	200 Ω	200 Ω

Connector pin**:

Product	SC 260/SC 660 Series	SC 230/SC 630 Series	SC 260 ATC/C3 UT
Pin 1	Mic GND	Mic GND	Shield
Pin 2	Mic +	Mic +	Red
Pin 3	SPK R***	SPK R***	Green
Pin 4	SPK L***	SPK L***	Black
Pin 5	SPK GND	SPK GND	White


* Limited by EPOS ActiveGard®

** Seen from front of mini-XLR

*** L = mic boom arm side. R = opposite mic boom arm side



Leatherette ear pads for maximized comfort



Delivered with mini XLR plug